


BBB12 12Volt 12Ah



SPECIFICATIONS

Nominal Voltage (V) **12V**

Nominal Capacity

20 hour rate	(0.06A to 10.50V)	12Ah
10 hour rate	(0.114A to 10.50V)	11.4Ah
5 hour rate	(0.204A to 10.20V)	10.2Ah
1 C	(1.2A to 9.60V)	6.8Ah
3 C	(3.6A to 9.60V)	4.8Ah

Weight Approx. **4.1Kg (9.02lbs)**

Internal Resistance (at 1KHz) Approx **13mΩ**

Maximum Discharge Current for 5 seconds **180A**

Charging Methods at 25°C (77°F)

Cycle use:

Charging Voltage **14.4 to 15.0V**
 Coefficient -5.0mV/°C/cell

Maximum Charging Current **3.6A**

Standby use:

Float Charging Voltage **13.5 to 13.8V**
 Coefficient -3.0mV/°C/cell

Operating Temperature Range

Charge	-15°C (5°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

Charge Retention (shelf life) at 20°C(68°F)


1 month	92%
3 month	90%
6 month	80%

Case Material **ABS**

(Option: UL94 HB & UL94 V-0 flame retardant)

Terminal **F1 or F2 (Faston Tab 187 or 250)**

DIMENSIONS mm(inch)



Flexel (UK) Ltd
 Central House
 Top Station Road
 Brackley
 Northamptonshire
 NN13 7UG

Phone: +44 (0)1280 704141
Fax: +44 (0)1280 706373
email: sales@flexelmobility.com