

ELECTRIC VEHICLE

applications are wide and varied with many durability & power demands placed firmly on the batteries shoulders.

HAZE ELECTRIC
VEHICLE AGM always
delivers when you need it,
whatever your DC
requirement in general EV
applications.




Tough ABS case with INSERT TERMINALS as standard, smaller sizes with FASTON.

Special Active Material
Formulation & AGM Technology
delivers cranking amps, general
power and long/deep
discharges.

GOOD CYCLE LIFE and resistance to mechanical stress and the elements all in one battery.

	Dimensions mm - kg						Dimensions Inches - lbs							Cold Cranking Amps		
			Height	Height	Height				Height	Height	Height		20oC	0oC	-18oC	
	Length	Width	Auto	Insert	Battery	Weight	Length	Width	Auto	Insert	Battery	Weight	(68oF)	(32oF)	(0oF)	
HZB-EV12-33EX	195	130	1	163	160	11.6	7.68	5.12	ı	6.42	6.30	25.58	439	345	240	

			R	eserve	Capacit	y - Mir	าร	Capacity - Ampere Hour*							
	Volts	Thread size mm	75 Amps	25 Amps	20 Amps	15 Amps	8 Amps	100 Hr	48 Hr	20 Hr	10 Hr	5 Hr	3 Hr	1 Hr	
HZB-EV12-33EX	12	6	16	64	86	121	255	47.3	44.4	41.1	39.0	35.7	32.5	27.3	



EV Charging - To obtain maximum cycle life from your EV battery it is important that a suitable charging profile is used. For information about the Haze range of chargers and the Haze recommended charging profile contact your local Haze distributor.

130±1.5

NOTE: All Haze AGM batteries are true cycling batteries, plate chemistry is specifically for cyclic applications.

195±1.5

HAZE ELECTRIC VEHICLE AGM delivers maximum capacity within five cycles and keeps delivering long after the others are on the scrap heap. HAZE R&D has resulted in SPECIAL CHEMICAL and PROCESS technology to ensure consistency and performance.

091214